



US009638398B2

(12) **United States Patent**  
**Nicolai et al.**

(10) **Patent No.:** **US 9,638,398 B2**  
(45) **Date of Patent:** **\*May 2, 2017**

(54) **LIGHTING DEVICES**

(71) Applicant: **Apogee Translite, Inc.**, Deer Park, NY (US)

(72) Inventors: **Richard Nicolai**, St. James, NY (US);  
**Martin Gaon**, Merrick, NY (US)

(73) Assignee: **APOGEE TRANSLITE, INC.**, Deer Park, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/284,949**

(22) Filed: **May 22, 2014**

(65) **Prior Publication Data**

US 2014/0254132 A1 Sep. 11, 2014

**Related U.S. Application Data**

(63) Continuation of application No. 13/627,411, filed on Sep. 26, 2012, now Pat. No. 8,814,376.

(51) **Int. Cl.**

<b>F21V 21/00</b>	(2006.01)
<b>F21V 1/00</b>	(2006.01)
<b>F21V 5/00</b>	(2015.01)
<b>F21V 7/00</b>	(2006.01)
<b>F21V 13/04</b>	(2006.01)
<b>F21V 9/16</b>	(2006.01)
<b>F21S 9/02</b>	(2006.01)
<b>F21V 29/77</b>	(2015.01)
<b>F21Y 101/00</b>	(2016.01)
<b>F21Y 103/10</b>	(2016.01)
<b>F21Y 115/10</b>	(2016.01)

(52) **U.S. Cl.**

CPC ..... **F21V 13/04** (2013.01); **F21V 7/005** (2013.01); **F21V 7/0008** (2013.01); **F21V 9/16** (2013.01); **F21S 9/022** (2013.01); **F21V 29/777** (2015.01); **F21Y 2101/00** (2013.01); **F21Y 2103/10** (2016.08); **F21Y 2115/10** (2016.08); **Y10T 29/49716** (2015.01)

(58) **Field of Classification Search**

CPC .... **F21V 13/04**; **F21V 29/2206**; **F21V 7/0008**; **F21V 7/005**; **F21V 9/16**; **F21V 29/2237**; **F21Y 2103/003**; **F21Y 2101/02**; **F21S 9/022**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

6,515,313 B1	2/2003	Ibbetson et al.
6,600,175 B1	7/2003	Baretz et al.
6,657,236 B1	12/2003	Thibeault et al.

(Continued)

*Primary Examiner* — Donald Raleigh

(74) *Attorney, Agent, or Firm* — Tutunjian & Bitetto, P.C.

(57)

**ABSTRACT**

A lighting device includes a cover portion configured to have a hinged connection for mounting on a housing. The cover portion includes a light emitting diode (LED) and a mixing chamber having a reflective internal surface for receiving light from the LED. A phosphorescent lens is disposed opposite the LED and is configured to reflect light from the LED back to the mixing chamber and to emanate absorbed light from the lens to a surrounding region outside of the mixing chamber. An LED driver circuit is configured to power the LED, the LED driver circuit being electrically connected to a power source. Other embodiments are also disclosed.

**22 Claims, 9 Drawing Sheets**

